



INSTALLATION GUIDE

A90/J29 Toyota Supra B58
CTS-IT-348



20630 Mufford Crescent, Unit #309
Langley, British Columbia V2Y 2V9

www.CTSTURBO.com

WHAT IS INCLUDED

1. CTS heat shields
2. CTS temperature sensor housing
3. CTS silicone coupler
4. CTS high flow air filter
4. Weather stripping
5. Hardware



NOTES

Vehicle used in this guide is a 2020 A90 Toyota Supra. Always make sure the car is safe to work on. Do not work on the car until it has cooled down. We do not accept any liability for incorrect installation or damage during the install.

STEP 1

Remove the engine cover



STEP 2

Disconnect the temperature sensor



STEP 3

Loosen the clamp holding the stock air box to the resonator

**STEP 4**

Lift and remove the stock air box



STEP 5

Loosen the lower clamp holding the resonator to the turbo inlet and remove


**STEP 6**

Assemble the heat shield and weather stripping



STEP 6

Install the heat shield into corresponding mounting points

**STEP 7**


Install the longer silicone coupler on to the turbo inlet, you may tighten the lower clamp at this time



STEP 8

Move the temperature sensor from the stock air box to the CTS housing with the provided allen bolts. Make note of the orientation, it only goes on one way.

Install the housing



STEP 9

Install the shorter silicone coupler and velocity stack.

You may tighten the clamps



STEP 10

Install the filter onto the velocity stack and tighten the clamp.

Check all clamps are secure and the temperature sensor is connected



STEP 11

Reinstall the engine cover and you are done!

